






Description	order code	Color	Application
20MM dia. Lamp support (PC-UV stabilised) 1) 40MM height 2) 60MM height 3) 80MM height (standard)	20 PC 40 20 PC 60 20 PC 80	Clear	for indoor & outdoor 
Silicone HT Cable (flame retardant) 1) 6.0MM O/D dia. 2) 7.0MM O/D dia.	SHT 60 Wh SHT 70 Wh	White	for indoor & outdoor 
Double-insulated 1.25MM (loop return cable) 4.5MM O/D dia.	DI 12 Wh	White	for indoor & outdoor 
Silicone End Caps (electrode caps) 1) 16MM i/D dia. 2) 18MM i/D dia.	SEC 16 Wh SEC 18 Wh	White	for indoor & outdoor 
Surge Protectors (for electronic transformers) 4.5 A load (installed parallel to mains)	S Pro	White	for indoor & outdoor  26mm X 70 mm

Description	order code	Color	Application
F.A.R.T Magnetic Transformers			<i>for indoor & outdoor</i>
1) 10kV-120mA	FT 10-120	Resin Block Grey	 <p>RESIN BLOCK</p> <p>Weatherproof IP 44 rated For indoor installations ceiling access REQUIRED</p> <p>  </p>
2) 10kV~ 90mA	FT 10-90		
3) 5kV~90mA	FT 5-90		
4) 3kV~90mA	FT 3-90		
5) 15kV~60mA	FT 15-60		
6) 12kV~60mA	FT 12-60		
7) 10kV~60mA	FT 10-60		
8) 7.5kV~60mA	FT 7-60		
9) 5kV~60mA	FT 5-60		
10) 3kV~60mA	FT 3-60		
11) 15kV~30mA	FT 15-30		
12) 12kV~30mA	FT 12-30		
13) 10kV~30mA	FT 10-30		
14) 7.5kV~30mA	FT 7-30		
15) 5kV~30mA	FT 5-30		
16) 3kV~30mA	FT 3-30		
Electronic Transformers			<i>for indoor & outdoor</i>
1) 8kV-50mA	MAXI 80 50	ABS White	 <p>Weatherproof IP 65 rated, solid state high frequency. Available in standard or dimmable 0-10V units For indoor installations ceiling access NOT required</p> <p>  </p>
2) 5kV~ 50mA	MAXI 50 50		
3) 3kV~50mA	MIDI 30 50		
4) 2kV~50mA	MIDI 20 50		
5) 3kV~80mA	MAXI 30 80		
6) 990V~100mA	MIDI 990 100		
7) 990V~100mA twin	MIDI 990 100 tw		
8) 900V~180mA	MIDI 990 180		
9) 12kV~35mA	MAXI 120 35		
10) 8kV~35mA	MAXI 80 35		
11) 5kV~35mA	MIDI 50 35		
12) 3kV~35mA	MINI 30 35		